

# VERMONT NATURAL COATINGS®

## PolyWhey®

*Professional Wood Finish Made Green.™*

*PolyWhey®, a revolutionary, patented technology delivers durable, safe and easy to use paints, stains and finishes that have established the highest performance and environmental standards. PolyWhey uses whey protein- a byproduct of cheese making- as the transformative ingredient.*

### A Better Whey



#### **Superior Durability**

Premium durability with our innovative PolyWhey formula.



#### **Safe For People and Pets**

No harsh fumes, low odor, waterbased, low VOCs.



#### **Made in the USA**

Contains agriculturally sourced and sustainable ingredients.



#### **Ultra-Low VOCs**

Complies with VOC laws in all 50 states and Canada.



#### **Green Innovation**

Made from the latest in green technology. Carbon neutral.

### PolyWhey® PaintPlus Paint Additive



Photo by Christa Grover

Blending Vermont Natural Coatings PaintPlus into latex paint creates an extraordinary experience. Our proprietary PolyWhey® technology creates a superior paint finish with unparalleled appearance and hand. From application to finished product, PolyWhey PaintPlus enhances painting with improved flow, leveling, sanding and overall performance greater than paint alone.

*Durable • Safe • Easy to use*

**Vermont Natural Coatings, Inc**

[www.VermontNaturalCoatings.com](http://www.VermontNaturalCoatings.com)

[info@VermontNaturalCoatings.com](mailto:info@VermontNaturalCoatings.com)

(802) 472-8700 Find us on

# VERMONT NATURAL COATINGS®

## PolyWhey®

### PAINTPLUS PAINT ADDITIVE

By using whey protein as a co-binder, PolyWhey leverages a renewable resource to deliver the safest and most durable paints, stains and finishes on the market.

#### RECOMMENDED USES:

Add PaintPlus to latex paint when painting cabinets, trim, and floors.



Available in Quarts

- Improves paint performance
- Neutral odor
- Non-flammable
- Hardens paint
- Creates better flow
- Ultra-low VOC



*Durable • Safe • Easy to use*

#### DIRECTIONS FOR USE

##### APPLICATION:



1) Stir well prior to use.



2) Use 1 quart with every ¾ gallon of paint. Mix thoroughly. Additional PaintPlus may be added for heavier use or higher traffic surfaces.

3) PaintPlus may reduce paint cover and impart slight color reduction. Always test a sample area before applying to whole surface.

4) Clean up with soap and water.

#### TECHNICAL DATA

Color in Container	Milky White
Clarity (Dry)	Crystal Clear
Chemical Resistance	No visual defects
VOC	≤50g/L (as packaged)
Flash Point	None
Freeze/Thaw Stability	Do not freeze
Pot Life	12 months from date of manufacture
Viscosity (#2 Zahn Cup)	20-30 sec.
Clean Up	Soap and hot water
Odor	Odor Neutral
Density	1.03 g/cm³
Weight Solids	≥ 36%
Volume Solids	≥ 34%

**Vermont Natural Coatings, Inc**

info@VermontNaturalCoatings.com

(802) 472-8700 Find us on

For project ideas and testimonials visit: [www.vermontnaturalcoatings.com](http://www.vermontnaturalcoatings.com)