


Authentic Oil-Based Look

The new standard in wood floor sealers

- A single component grain enhancing sealer that creates an authentic oil-based look.
- Safe, durable, and easy to apply. Made with PolyWhey® and Climate Cool plant-based resins.
- Unlike other wood floor sealers, it meets the highest professional application and environmental standards, without compromising performance and durability. Hydro Seal gives wood a warm amber appearance making it the exclusive alternative to harmful solvent-based finishes.







VERMONT NATURAL COATINGS, INC
TEL: 802.472.8700
TOLL FREE: 888.639.9439
info@vermontnaturalcoatings.com
vermontnaturalcoatings.com
@ Vermont Natural Coatings, 2021

Visit **www.vermontnaturalcoatings.com** for videos, instructions, technical data, safety information, case studies, and more.

PolyWhey® is a registered trademark of Vermont Natural Coatings, Inc.



PolyWhey HYDRO SEAL Professional Wood Floor Sealer

FEATURES & BENEFITS

- Single-Component formulation means no wasted sealer
- Superior flow and leveling results in easy application and evenly sealed floors
- At 250 g/L, PolyWhey Hydro Seal complies with all US and Canadian VOC regulations
- Fast drying time offers the ability to apply up to 2 coats of sealer in one day.
- Neutral odor allows for coating in occupied areas without disrupting residents/visitors
- With no carcinogens or isocyanates, PolyWhey Hydro Seal has no flash point and will not contribute toward cancer or fire risks. Hydro Seal is a USDA Certified Biobased Product.

AVAILABILITY

UPC-A Vermont Natura	DESCRIPTION Il Coatings Hydro Sea		PKS/CS	CASE WT. (LBS.)	CASE DIMENSIONS
817511 01890 1	Sealer- 1 Gallon	1	4	38	11" x 14.5" x 10"
817511 01889 5	Sealer - 1 Gal. CASE	1 CASE	n/a	38	11" x 14.5" x 10"
817511 01891 8	Sealer - 5 Gallon	1	n/a	45	15" x 12" x 12"

TECHNICAL DATA

Color in Container Clarity (Dry) Chemical Resistance VOC

Flash Point
Freeze/Thaw Stability
Pot Life
Dry Time
Clean Up
Odor
Maximum Cure
Coverage

Milky Liquid
Crystal Clear
No visual defects
Coating: ≤250g/L (wet)
Material: ≤18g/L (dry)
None
Do not freeze
12 months
1-2 hr. (normal conditions)
Soap and hot water
Slight odor
One week

500-600 sq. ft. per gallon

VALUE

SAFETY AND VALUE	Characteristic	PolyWhey HYDRO SEAL
	VOC in grams per liter	250
	Whey Technology	Yes
	Contains mutagen NMP	No
	Renewable content	Yes
	Coverage	500-600



VERMONT NATURAL COATINGS, INC
TEL: 802.472.8700
TOLL FREE: 888.639.9439
info@vermontnaturalcoatings.com
vermontnaturalcoatings.com
© Vermont Natural Coatings, 2021

Visit www.vermontnaturalcoatings.com for videos, instructions, technical data, safety information, case studies, and more.

PolyWhey® is a registered trademark of Vermont Natural Coatings, Inc.

