

PolyWhey®

SUNSEAL

Anti-Yellowing UV Protection

The new standard in professional wood floor sealers

- High tech anti-yellowing protection helps keep the natural look of raw wood.
- Safe, durable, and easy to apply. Made PolyWhey® and Böhme technology.
- Unlike other UV protectant wood floor sealers, it meets the highest professional application and environmental standards, without compromising performance and durability. SunSeal protects photosensitive wood against discoloration effects caused by sunlight and damaging UV rays.



BÖHME
SWISS QUALITY  SINCE 1866



VERMONT NATURAL COATINGS, INC
TEL: 802.472.8700
TOLL FREE: 888.639.9439
info@vermontnaturalcoatings.com
vermontnaturalcoatings.com
© Vermont Natural Coatings, 2021

Visit www.vermontnaturalcoatings.com
for videos, instructions, technical data, safety information,
case studies, and more.

PolyWhey® is a registered trademark of Vermont Natural Coatings, Inc.

VERMONT
NATURAL
COATINGS®

PolyWhey® SunSeal Anti-UV Professional Wood Floor Sealer

FEATURES & BENEFITS

- Ideal for UV protection for new or bare interior wood floors.
- Superior flow and leveling results in easy application and evenly protected floors
- At 30 g/L, SunSeal complies with all US and Canadian VOC regulations
- Fast drying time streamlines projects
- Neutral odor allows for coating in occupied areas without disrupting residents/visitors
- SunSeal has no flash point and will not contribute toward fire risk.

AVAILABILITY

UPC-A	DESCRIPTION	QTY/PK	PKS/CS	CASE WT. (LBS.)	CASE DIMENSIONS
Vermont Natural Coatings SunSeal					
817511 01887 1	Sealer - 1 Gallon	1	4	38	11" x 14.5" x 10"
817511 01886 4	Sealer - 1 Gal. CASE	1 CASE	n/a	38	11" x 14.5" x 10"
817511 01888 8	Sealer - 5 Gallon	1	n/a	45	15" x 12" x 12"

VALUE

SAFETY AND VALUE	Characteristic	PolyWhey SunSeal
	VOC in grams per liter	30
	Whey Technology	Yes
	Contains mutagen NMP	No
	Renewable content	Yes
	Coverage	300-400

TECHNICAL DATA

<i>Color in Container</i>	Milky White
<i>Clarity (Dry)</i>	Semi-Transparent
<i>Chemical Resistance</i>	No visual defects
<i>VOC</i>	Coating: 30g/L (wet)
<i>Flash Point</i>	None
<i>Freeze/Thaw Stability</i>	Do not freeze
<i>Pot Life</i>	12 months
<i>Dry Time</i>	6-12 hours
<i>Clean Up</i>	Soap and water
<i>Odor</i>	Neutral
<i>Maximum Cure</i>	One week
<i>Coverage</i>	300 - 400 sq. ft. per gallon



Untreated, naturally aged wood Treated with SunSeal

PolyWhey Pro Line - NEW PRODUCTS available now!

VERMONT NATURAL COATINGS, INC
 TEL: 802.472.8700
 TOLL FREE: 888.639.9439
 info@vermontnaturalcoatings.com
 vermontnaturalcoatings.com
 © Vermont Natural Coatings, 2021

Visit www.vermontnaturalcoatings.com
 for videos, instructions, technical data, safety information,
 case studies, and more.

PolyWhey® is a registered trademark of Vermont Natural Coatings, Inc.

VERMONT
 NATURAL
 COATINGS®